

AD Accessory U8

Overview

Frequency Band
UHF 860-960 MHz

Chip
NXP UCODE 8

Antenna Dimensions
30 x 15 mm / 1.20 x 0.60 in

International Standard
ISO 18000-63, EPC Class 1 Gen 2

Industry Segments
Apparel
Healthcare

Applications
Children Accessories
Fashion Jewelry and Sunglasses
Pharmaceutical and Healthcare

RoHS
EU Directive 2011/65/EC and
Directive (EU) 2015/863

REACH
Regulation (EC) No. 1907/2006



Ideal for small item-level tagging

Our AD Accessory U8 inlays and tags are optimized for accessory and cosmetics applications, offering excellent performance and superior close-coupling features.


AD Accessory products are equipped with NXP's UCODE® 8 IC. Inlays with UCODE 8 chip offers the same memory size and typical IC features as NXP UCODE 7. Furthermore, it offers a Self Adjust feature to maximize product performance in challenging environments and has an improved read and write sensitivity and faster encoding speed compared to NXP UCODE 7. Furthermore, the chip has an integrated Brand Identifier function to prove product authenticity and a memory safeguard system to protect business data. AD Accessory U8 products are available in dry, wet and paper tag delivery formats.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment.

Technical features

Chip	NXP UCODE 8	
EPC and User Memory	128-bit and 0	
TID Memory	96-bit / 48-bit unique serial number	
Product Code	3007174 / IL-603472	3007175 / IL-603473
Delivery Format	Wet inlay	Label
Die-Cut Dimension	33 x 18 mm / 1.30 x 0.70 in	
Inlay Substrate	PET	PET
Face Sheet	-	Mid-gloss paper
Standard Pitch	20 mm / 0.787 in	20 mm / 0.787 in
Web Width	36 mm / 1.4 in	36 mm / 1.4 in
Core Size	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	10,000 pcs/reel 30,000 pcs/box	5,000 pcs/reel 15,000 pcs/box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F	
Certificates	ARC Spec M and Q	

Read range



All graphs are indicative: performance in real life applications may vary.

Contact information

rfid.averydennison.com/contact
+1-678-617-2359

Connect with us on:



© 2022 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

