

865-870 MHz FORKLIFT MOUNT 6dBic CP RFID PANEL ANTENNA

The Laird S8656XR antenna gives RFID users an antenna that meets all of the criteria requirements for forklift RFID applications. At only 7.6 x 7.6 x .95", the antenna is small enough to accommodate a wide variety of forklift applications. The antenna provides 6dBi of gain in the 865-870 MHz band.

The antenna material construction is unique in that it is an all metal antenna. No exterior radome enclosure is required to protect critical components. The result is an antenna that is extremely robust and resistant to damage.

The antenna can be mounted directly to the forklift allowing for a view directly into any pallet. Two antennas can be mounted side-by-side on a custom configured mounting platform if that is desirable.

The antenna is provided with a plastic front panel that is secured with adhesive for the purposes of providing a surface that can be used for branding or for any other graphical element that the customer might desire.

FEATURES



- Low profile
- Extremely low VSWR
- Wide band
- Weather resistant radome
- Wide range of connector options

APPLICATIONS

- Direct forklift mount
- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyor belt

SPECIFICATIONS

Antenna Part Number	S8656XR
Frequency Range	865–870 MHz
Gain	6 dBi
Maximum VSWR	1.5:1
3 dB Beamwidth - Azimuth	80°
Front-to-Back Ratio	8 dB
Polarization	Circular right-hand
Maximum Input Power	4 Watts
Input Impedance	50 Ohms
Axial Ratio	3 dB Typical
Weight (Kg)	2.6 lbs (1.2)
Mechanical Size	7.59 x 7.59 x .95"
Antenna Connection	Right angle Type N Female Other configurations available by request
Radome	Aluminum w/minimal Polycarbonate
Mount Style	Chassis mount
Temperature Operational	-30°C to +70°C
Lightning Protection	DC grounded
Water/Foreign Body Ingress	IP67

Systems-US-Sales@lairdtech.com
+1.724.962.3571
+1.760.737.7800

Systems-CDN-Sales@lairdtech.com
+1.504.908.1659

Systems-EU-Sales@lairdtech.com
+49.2161.6363.0

Systems-UK-Sales@lairdtech.com
+44.0.1932.247.511

Systems-CN-Sales@lairdtech.com
+86.21.3120.0188


Systems-SA-Sales@lairdtech.com
+27.11.425.1123

Systems-BR-Sales@lairdtech.com
+55.19.3243.7803


www.lairdtech.com

S8656XR

Metal CP RFID Panel Antenna



Right-hand circularly polarized
linear azimuth plot.



Right-hand circularly polarized
linear elevation plot

ANT-DS-S8656XR_071514

Any information furnished by Laird and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird, Laird Technologies, Inc or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.